

# STROMTANK

AUDIO POWER

## International specifications

## Stromtank S5000

### Input AC parameters on grid

Input voltage range	50 to 140 Vac / 150 to 265 Vac
Input frequency	45 to 65 Hz (auto sensing)
Input current max.	16 Aac (transfer relay)
Input current adjusted	10 Aac (115Vac), 10 Aac (230Vac) – factory setting
transfer time	< 15 ms, on grid to off grid

### Output AC parameter off grid

Output voltage	100-130Vac / 200-245Vac (pure sine wave +/- 2%)
Output frequency	50 Hz / 60 Hz +/- 0.05% (crystal controlled)
Harmonic distortion	< 2%
Continues power @ 25°C	750 VA
Power 30min. @ 25°C	1.200 VA
Maximum load	up to short circuit
Maximum asymmetric load	up to P cont.
Load detection (Stand by)	10 W
Cos $\varphi$	0.1 – 1
Maximum efficiency	93% (dc/ac conversion mode)
Consumption stand-by/on	2 W / 8 W
Overload + short-circuit protection	automatic disconnecting with 3 restart attempts
Overheat protection	warning before shut-down with automatic restart
Operating temperature	+10 to 45°C
Relative Humidity	0 to 85% non- condensing
Acoustic level	< 40 dB

# STROMTANK

---

AUDIO POWER

---

## Battery power unit

Battery type	LFP - Lithium Iron Phosphate (LiFePO4)
Nominal battery voltage	48 / 50 Vdc
Nominal capacity	100 Ah
Volume Energy Density	177 Wh/l
Gravimetric Power Density	107 Wh/kg
Typical charge current	8 Adc - factory setting
Working temperature	0 to 45°C, 32 to 113°F
Emergency charge current	3 Adc (special STROMTANK charger necessitated)*
Battery Management System	Flex-BMS, single cell control, active balancing 5A

## Terminal area

AC output receptacles	3x Hubbell duplex, Hospital spec. grade 3x Furutech High performance Schuko sockets
AC output fuse	thermal – magnetic circuit breaker
AC input connection	ICE 320 - C14 (fuse 16/10AT)
Interface	CAN (RJ45-8 type “Com bus”)*, USB*
Charge connector	use STROMTANK charger only
Power switch	on/off (“on” = green LED)
Safety key switch	key switch “Release/Lock” all functions**

## Additional Features

Color	meteorit-gray (other colors on request)
Weight	115 kg / 255 lbs
Dimension (w x h x d)	48 x 58 x 59 cm / 19 x 22.8 x 23.2 inches

\* only for use with “STROMTANK” software and charger

### \*\* ATTENTION

You have to switch **OFF** STROMTANK with the “main switch” before locking.  
You have to unlock before switch **ON** STROMTANK.